



VISHAY INTERTECHNOLOGY, INC.



## PRECISION POTENTIOMETERS

Wirewound Technology, Single- and Multi-Turn Models

RESISTIVE PRODUCTS

SELECTOR GUIDE



# Precision Potentiometers

Wirewound Technology, Single- and Multi-Turn Models

## FEATURES

- Large electrical angles
- High power dissipation
- Low temperature coefficient

## APPLICATIONS

- Temperature control for industrial refrigerators
- CCTV cameras
- Industrial machines for welding and wire cutting
- Medical equipment (X-ray machines)

Model	Electrical Travel (°)	High Accuracy (Linearity)	Ohmic Values (ohms)	Resistance Tolerance at 20 °C	Starting Torque (N.cm)	Operating Life (Cycles)	Temperature Range (°C)	Cylindrical External Diameter (mm)	Options
100	352° ± 2° (single turn)	± 0.5%, 100 < Rt < 35K ± 1.0%, 5 < Rt < 100	5 to 35 K	± 3%, 50 < Rt ± 5%, 5 < Rt < 50	< 0.45 (Servo) < 0.75 (Bushing) < 0.25 (Each add.)	1 million	- 55 °C to + 105 °C	33.3	Up to 6 sections
122	350° ± 2° (single turn)	± 0.5%, 200 < Rt < 100K ± 1.0%, 5 < Rt < 200	5 to 100 K	± 3%, 20 < Rt < 100K ± 5%, 5 < Rt < 20	< 0.2 (Servo) < 0.25 (Bushing) < 0.15 (Each add.)	1 million	- 55 °C to + 125 °C	27	Up to 6 sections
132	352° ± 2° (single turn) bushing mount	± 0.5%, 200 < Rt < 35K ± 1.0%, 5 < Rt < 200	5 to 35 K	± 3%, 50 < Rt < 35K ± 5%, 5 < Rt < 50	< 0.75	500000	- 55 °C to + 125 °C	33.3	Stops on request
140	320° ± 5° (single turn) bushing mount	± 1%	50 to 20 K	± 5%	< 0.15	500000	- 55 °C to + 125 °C	12.7	Sealed on request
142	350° + 0° - 4° (single turn) servo mount	± 1%	50 to 20 K	± 5%	< 0.06	500000	- 55 °C to + 125 °C	12.7	Sealed on request
152	340° ± 2° (single turn)	± 0.5%, 500 < Rt < 40K ± 1.0%, 5 < Rt < 500	5 to 40 K	± 3%, 50 < Rt < 40K ± 5%, 5 < Rt < 50	< 0.2 (Servo) < 0.25 (Bushing)	2 million (Servo) 1 million (Bushing)	- 55 °C to + 125 °C	22.2	-
202	350° ± 2° (single turn)	± 0.25%, 500 < Rt < 65K ± 0.5%, 50 < Rt < 500 ± 1%, 5 < Rt < 50	5 to 65 K	± 3%, 50 < Rt < 65K ± 5%, 5 < Rt < 50	< 0.50 (Servo) < 0.75 (Bushing) < 0.30 (Each add.)	1 million	- 55 °C to + 125 °C	44.5	Up to 6 sections
302	350° ± 2° (single turn)	± 0.25%, 200 < Rt < 85K ± 0.5%, 50 < Rt < 200 ± 1%, 5 < RT < 50	5 to 85 K	± 3%, 50 < Rt < 85K ± 5%, 5 < Rt < 50	< 0.75 (Servo) < 1.25 (Bushing) < 0.45 (Each add.)	1 million	- 55 °C to + 125 °C	50.8	Up to 6 sections
402	350° ± 2° (single turn)	± 0.25%, 200 < Rt < 150K ± 0.5%, 10 < Rt < 200	10 to 150 K	± 3%, 100 < Rt < 150K ± 5%, 10 < Rt < 100	< 0.80 (Servo) < 1.40 (Bushing) < 0.60 (Each add.)	1 million	- 55 °C to + 125 °C	76.2	Up to 6 sections
702	350° ± 2° (single turn)	± 0.5%, 500 < Rt < 100K ± 1.0%, 5 < Rt < 500	5 to 100 K	± 3%, 20 < Rt < 100K ± 5%, 5 < Rt < 20	< 0.10 (Servo) < 0.20 (Bushing) < 0.10 (Each add.)	1 million	- 55 °C to + 125 °C	22.2	-
162	3600° + 15° - 0° (10 turns) bushing mount	± 0.30%	100 to 115 K	± 5%	< 0.60	500000	- 55 °C to + 125 °C	12.7	-



Model	Electrical Travel (°)	High Accuracy (Linearity)	Ohmic Values (ohms)	Resistance Tolerance at 20 °C	Starting Torque (N.cm)	Operating Life (Cycles)	Temperature Range (°C)	Cylindrical External Diameter (mm)	Options
164	3600° + 15° - 0° (10 turns) servo mount	± 0.30%	100 to 115 K	± 5%	< 0.30	500000	- 55 °C to + 125 °C	12.7	-
502	3600° + 4° - 0° (10 turns)	± 0.25%	15 to 150 K	± 3%, 100 < Rt < 150K ± 5%, 15 < Rt < 100	< 0.30 (Servo) < 0.40 (Bushing) < 0.25 (Each add.)	2 million	- 55 °C to + 125 °C	22.2	Up to 2 sections
533	1080° + 0° + 10° (3 turns)	± 0.25%	50 to 20 K (60 K)	± 5%	< 0.50 (One section) < 0.80 (Two sections)	300000	- 55 °C to + 125 °C	22.2	Up to 2 sections
534	3600° + 0° + 10° (10 turns)	± 0.25%	100 to 100 K (200 K)	± 5%	< 0.35 (One section) < 0.65 (Two sections)	1 million	- 55 °C to + 125 °C	22.2	Up to 2 sections
535	1800° + 0° + 10° (5 turns)	± 0.25%	50 to 50 K (100 K)	± 5%	< 0.50 (One section) < 0.80 (Two sections)	500000	- 55 °C to + 125 °C	22.2	Up to 2 sections
536	3600° + 0° + 10° (10 turns)	± 0.25%	100 to 100 K	± 5%	< 0.40	1 million	- 55 °C to + 125 °C	22.2	-
552	1080° + 4° - 0° (3 turns)	± 0.25%	5 to 45 K	± 3%, 50 < Rt < 45K ± 5%, 5 < Rt < 50	< 0.30 (Servo) < 0.40 (Bushing) < 0.25 (Each add.)	600000	- 65 °C to +125 °C	22.2	-
802	3600° + 4° - 0° (10 turns)	± 0.25%	20 to 500 K	± 3%, 200 < Rt < 500K ± 5%, 20 < Rt < 200	< 0.90 (Servo) < 1.30 (Bushing) < 0.60 (Each add.)	2 million	- 55 °C to + 125 °C	50.8	Up to 3 sections
830	1080° + 4° - 0° (3 turns) bushing mount	± 0.25%	15 to 150 K	± 3%, 200 < Rt < 150K ± 5%, 15 < Rt < 200	< 1.30 (One section) < 1.90 (Two sections)	500000	- 55 °C to + 125 °C	46	Up to 2 sections
852	1080° + 4° - 0° (3 turns)	± 0.25%	15 to 150 K	± 3%, 100 < Rt < 150K ± 5%, 15 < Rt < 100	< 0.90 (Servo) < 1.30 (Bushing) < 0.6 (Each add.)	600000	- 55 °C to + 125 °C	46	Up to 3 sections
860	3600° + 4° - 0° (10 turns) bushing mount	± 0.25%	20 to 500 K	± 1%, 200 < Rt < 500K ± 3%, 20 < Rt < 200	< 1.30 (One section) < 1.90 (Two sections)	500000	- 55 °C to + 125 °C	46	Up to 2 sections

#### SEMICONDUCTORS:

Rectifiers • Small-Signal Diodes • Zener and Suppressor Diodes • MOSFETs  
• RF Transistors • Optoelectronics • ICs

#### PASSIVE COMPONENTS:

Resistive Products • Magnetics • Capacitors • Strain Gages and Instruments  
• PhotoStress® Instruments • Transducers



## One of the World's Largest Manufacturers of Discrete Semiconductors and Passive Components

WORLDWIDE SALES CONTACTS

### THE AMERICAS

#### UNITED STATES

VISHAY AMERICAS  
ONE GREENWICH PLACE  
SHELTON, CT 06484  
UNITED STATES  
PH: +1-402-563-6866  
FAX: +1-402-563-6296

### ASIA

#### SINGAPORE

VISHAY INTERTECHNOLOGY  
ASIA PTE LTD.  
25 TAMPINES STREET 92  
KEPPEL BUILDING #02-00  
SINGAPORE 528877  
PH: +65-6788-6668  
FAX: +65-6788-0988

#### P.R.C.

VISHAY INTERTECHNOLOGY  
ASIA PTE. LTD.  
(SHANGHAI REPRESENTATIVE OFFICE)  
ROOM D,15F, SUN TONG INFOPORT PLAZA  
55 HUAI HAI WEST ROAD  
200030 SHANGHAI  
P.R.C.  
PH: +86-21-6283-1036  
FAX: +86-21-6283-1039

#### JAPAN

VISHAY JAPAN CO., LTD.  
GE EDISON BUILDING, SHIBUYA 3F  
3-5-16 SHIBUYA  
SHIBUYA-KU  
TOKYO 150-0002  
JAPAN  
PH: +81-3-5464-6411  
FAX: +81-3-5464-6433

### EUROPE

#### GERMANY

VISHAY EUROPE SALES GMBH  
GEHEIMRAT-ROSENTHAL-STR. 100  
95100 SELB  
GERMANY  
PH: +49-9287-71-0  
FAX: +49-9287-70435

#### FRANCE

VISHAY S.A.  
199, BLVD DE LA MADELEINE  
06003 NICE, CEDEX 1  
FRANCE  
PH: +33-4-9337-2920  
FAX: +33-4-9337-2997

#### NETHERLANDS

VISHAY BCCOMPONENTS B.V.  
HURKESTRAAT 31  
P.O. BOX 8766  
5652 AH EINDHOVEN  
NETHERLANDS  
PH: +31-40-2590-700  
FAX: +31-40-2590-777